

BERESKIN & PARR

BOX 401, 40 KING STREET WEST, TORONTO, CANADA M5H 3Y2
PHONE (416) 364-7311 • FAX (416) 361-1398 • WWW.BERESKINPARR.COMPlease type a plus sign (+) inside this box → ☒PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.UTILITY
PATENT APPLICATION
TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 5562-740/PMdC

First Inventor or Application Identifier CONRAD et al

Title METHOD AND APPARATUS FOR PURIFYING WATER

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 21]
(preferred arrangement set forth below)
- Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Micro fiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 1]
4. Oath or Declaration [Total Pages 4]
- a. ☒ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
- i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting
inventor(s) named in the prior application,
see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney
(when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement(s) ☐ Statement filed in prior application,
(PTO/SB/09-12) Status still proper and desired
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Other:

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____

Prior application information: Examiner _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Labelor ☒ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name	Bereskin & Parr				
Address	Box 401 40 King Street West				
City	Toronto	State	Ontario	Zip Code	M5H 3Y2
Country	Canada	Telephone	(416) 364-7311	Fax	(416) 361-1398

Name (Print/Type)	Philip C. Mendes da Costa	Registration No. (Attorney/Agent)	33,106
Signature		Date	Jan/29/99

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Office, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

BP #5562-740

BERESKIN & PARR

United States

Title: METHOD AND APPARATUS FOR PURIFYING WATER

Inventor(s): Wayne Ernest Conrad
Helmut Gerhard Conrad
Ted Szylowiec

Title: METHOD AND APPARATUS FOR PURIFYING WATER

FIELD OF THE INVENTION

5 This invention relates of an apparatus for treating water with a gas containing ozone. The apparatus may be used in the production of water fit for human consumption from water contaminated by microorganisms, chemicals, heavy metals and minerals. The gas containing ozone may be present either by itself or in
10 combination with one or more other gasses and/or a liquid. Further, the water may be present by itself or may also have one or more liquids and/or one or more other gases associated therewith.

BACKGROUND OF THE INVENTION

15 The production of water suitable for human consumption from water contaminated by one or more of microorganisms, chemicals, heavy metals and minerals is a requirement throughout the world. Many different proposals have been made for the purification of contaminated water.

20 A popular system in widespread use for the purification of contaminated water is a filtration based system. Such systems use a filter made from a combination of a porous media filter, activated carbon, and an ion exchange resin through which the contaminated water is passed. The filtered water is typically fed into a clean water
25 reservoir. This type of system will reduce the levels of chlorine, lead, and pesticides. However, there are several disadvantages associated with this device.

 The first disadvantage of this water purification system is that the structure of the filter provides a breeding ground for
30 microorganisms thereby multiplying the dangers of microorganisms which may be present in very low numbers. Another disadvantage of such a water purification system is that the filter life is not measured and it is possible for the user to employ the filter beyond its useful life. A further disadvantage of such a water purification system is that oils

and fuels often present in water drawn from lakes and rivers are not readily removed. Further, these oils and fuels tend to coat the filters and damage their operational life and effectiveness. Some filtration based products now incorporate a means of measuring the water
5 volume passing through the filter and an indicator as to when to change the filter. Other filters incorporate an iodine product to minimize the risk of microbiological hazards, however, these materials often impart undesirable tastes and many are potential carcinogens.

Another popular system in use for the purification of
10 contaminated water is a system which employs ultraviolet light for disinfection in series with a porous media and carbon filter. This type of system will reduce the levels of chlorine, lead, and pesticides and has some disinfection capability. One disadvantage with this system is that the ultraviolet light's disinfection efficacy is greatly diminished by
15 turbidity or color in the water which can cause the filter to become contaminated by microorganisms which can readily live and breed therein thereby multiplying the danger from any microorganisms which may be present. Thus, the filter of this system also suffers from the disadvantages associated with filters of filtration based systems.

20 Contaminated water may also be treated to obtain drinking water by passing ozone through the water to kill microorganism contaminants such as bacteria present in the water. Various processes to treat water have been developed using combinations of filtration and ozonation.

25 For example, United States Patent No. 5,683,576 to Olsen describes an apparatus for treating contaminated water by passing ozone through the water. In the system disclosed by Olsen, an ozone containing gas is passed through the water to be treated, until the instantaneous concentration of ozone in the head space above the
30 water being treated reaches a predetermined level. Then, the flow of ozone through the water continues for a predetermined period of time.

The amount of ozone which must be passed through the water to purify it to any particular state will vary depending upon the initial quality of water to be treated. For example, untreated well or lake water may require a higher degree of purification than treated city
5 water which has previously been treated to some degree.

One disadvantage of Olsen is that it can not be reliable used with such disparate types of water supply. Olsen does not monitor the total amount of ozone which passes through the water unreacted. Thus, the actual degree of treatment of the water is not measured. The
10 system is designed only to ensure that a predetermined minimum amount of ozone passes through the system unreacted. The system makes the assumption that once the concentration of ozone reaches the predetermined level, that it does not subsequently drop below that level, or rise above that level. Further, it assumes that once the water to
15 be treated has been exposed to the preset ozone concentration for a predetermined time that the water is suitable for use. However, depending on the degree of contamination of the water to be treated, the time required to treat the material will vary.

In Olsen, the amount of unreacted ozone passing through
20 the system prior to the time when the instantaneous concentration reaches the predetermined level is not measured. Further, the amount of unreacted ozone passing through the system measured during the predetermined amount of time after the predetermined instantaneous concentration is reached is not measured. Thus, the actual degree of
25 treatment of the water is not measured.

SUMMARY OF THE INVENTION

In accordance with the instant invention, there is provided a method of treating a liquid comprising water with a gas
30 comprising ozone, the method comprising the steps of:

(a) providing the liquid in a treatment vessel;

(b) introducing the gas into the vessel to treat the liquid in the treatment vessel to obtain treated liquid;

(c) increasing the pressure in the treatment vessel; and

5 (d) utilizing the increased pressure in the treatment vessel to dispense the treated liquid from the treatment vessel.

In one embodiment, the method further comprises the step of venting at least a portion of the gas from the treatment vessel during step (b). The pressure in the treatment vessel is preferably increased by reducing the amount of gas which is being vented from
10 the treatment vessel.

In another embodiment, the method further comprises the step of passing the treated liquid through a filter located downstream from the treatment vessel during step (d). At least a portion of the gas vented from the treatment vessel during step (b) may
15 be passed through the filter, and preferably all of the vented off gas is passed through the filter.

One advantage of this method is that the ozone which remains in the off gas may be used to treat the filter and reduce or prevent the growth of microorganisms in the filter. Therefore, it is
20 preferred that all or essentially all of the gas introduced into the treatment vessel is passed through the filter during the treatment cycle. However, during the initial stages of the treatment cycle, the treatment vessel may be sealed (i.e. some or all of the off gas maybe retained in the vessel) to increase the operating pressure of the treatment vessel.
25 Once a desired pressure is achieved, the off gasses may be vented to treat the filter while maintaining the treatment vessel at the elevated pressure.

In another embodiment, the method further comprises the step of automatically dispensing the treated water when the
30 pressure in the treatment vessel reaches a preset level.

In another embodiment, the method further comprises

the step of introducing the gas into the treatment vessel as bubbles.

In another embodiment, the method further comprises the step of treating the liquid with the gas until a prespecified condition is met, the prespecified condition selected from the group:

- 5 (a) until a predetermined level of treatment of the liquid is achieved, or
 - (b) for a predetermined time, or
 - (c) until the treatment of the liquid does not match a preset treatment profile.
- 10 A user may be signalled if a predetermined level of treatment of the liquid is not achieved in the predetermined time or if the treatment profile is not achieved. This may be achieved by measuring the ozone concentration in the off gas in the treatment vessel and signalling the user if the concentration of ozone in the off gas is higher than that of
- 15 the treatment profile. Alternately, or in addition, the user may be signalled if the concentration of ozone in the off gas is lower than that of the treatment profile.

In another embodiment, the method further comprises the step of monitoring the treatment of the liquid and preventing the

20 liquid from being dispensed from the treatment vessel if a predetermined level of treatment of the liquid is not achieved.

In accordance with another embodiment of the instant invention, there is provided an apparatus for treating a liquid comprising water with a gas comprising ozone, the apparatus

25 comprising:

- (a) a treatment vessel having at least one inlet port for introducing the gas and the liquid into the vessel and, a gas outlet port for removing gas from the vessel;
- (b) a pressurized source of the gas for treating the liquid in
- 30 communication with gas inlet port;
- (c) a first passageway for dispensing treated liquid from the

treatment vessel during a dispensing cycle, the passageway having a first valve operable between a first open position and a second closed position;

5 (d) a second valve associated the gas outlet port and having a first open position for allowing the off gas to vent from the treatment vessel and a second open position for preventing the off gas to vent from the treatment vessel

10 whereby when the pressure in the treatment vessel reaches a predetermined level, the first valve automatically moves to the open position to cause treated liquid to flow from the treatment vessel through the first passageway.

15 In one embodiment, the apparatus further comprises a filter positioned downstream from the treatment vessel and the predetermined pressure level is determined based on the pressure required to cause the treated water to flow through the filter. The apparatus may have a second passageway in flow communication with the second valve and the filter for venting the off gas through the filter.

20 In another embodiment, the liquid in the treatment vessel is subjected to a treatment cycle and at the end of the cycle, the second valve is moved towards the closed position to increase the pressure in the treatment vessel to the predetermined level. The second valve may be a pressure actuated valve such as a spring actuated valve or a check valve. Alternately, the valve may be electronically controlled by a
25 controller and the apparatus may include a pressure sensor for monitoring the pressure in the treatment vessel and signalling the controller when a predetermined pressure is reached.

In another embodiment, the apparatus further comprises an ozone generator located in flow communication with the inlet port.
30 In addition, the apparatus may further comprise an oxygen concentrator located upstream of and in flow communication with the

ozone generator.

In another embodiment, the apparatus further comprises a controller for monitoring the treatment of the water in the treatment vessel with the gas until a prespecified condition is met, the
5 prespecified condition selected from the group:

- (a) until a predetermined level of treatment of the liquid is achieved, or
- (b) for a predetermined time, or
- (c) until the treatment of the liquid does not match a
10 preset treatment profile.

In one embodiment, the apparatus further comprises a warning signal to advise a user if a predetermined level of treatment of the liquid is not achieved in the predetermined time or if the treatment profile is not achieved. The apparatus may have a sensor for measuring the
15 ozone concentration in the off gas in the treatment vessel and a warning signal for advising a user if the concentration of ozone in the off gas is higher than that of the treatment profile. Alternately, or in addition, the apparatus may have a warning signal for advising a user if the concentration of ozone in the off gas is lower than that of the
20 treatment profile.

In another embodiment, the apparatus further comprises an actuator for commencing the dispensing cycle, a controller for monitoring the treatment of the liquid and preventing the liquid from being dispensed from the treatment vessel if a predetermined level of
25 treatment of the liquid is not achieved.

In accordance with another embodiment of the instant invention, there is provided an apparatus for treating a liquid comprising water with a gas comprising ozone, the apparatus comprising:

- 30 (a) retaining means for retaining the liquid during a treatment cycle of the liquid with the gas;

(b) means for introducing the gas under pressure into the retaining means to obtain treated liquid;

(c) venting means for removing off gas from the retaining means;

5 (d) means for increasing the pressure in the retaining means at the end of a treatment cycle; and,

(e) dispensing means for automatically removing treated liquid from the retaining means during a dispensing cycle when the pressure in the retaining means reaches a
10 predetermined level.

At the end of the treatment cycle, the venting means may be interrupted (eg. closed) to increase the pressure in the retaining means to the predetermined level.

In one embodiment, the apparatus further comprises
15 means for actuating the dispensing cycle and means for preventing the liquid to be dispensed from the retaining means if a predetermined level of treatment of the liquid is not achieved.

BRIEF DESCRIPTION OF THE DRAWINGS

20 A further, detailed description of the invention, briefly described above, will follow by reference to the following drawings of a preferred embodiment of the invention in which:

Figure 1 shows a schematic representation of an apparatus according to the instant invention.

25

DESCRIPTION OF PREFERRED EMBODIMENT

Figure 1 schematically illustrates a system for treating a liquid comprising water with a gas comprising ozone. Preferably the liquid consists of water and the gas comprises air containing ozone.
30 Accordingly, the apparatus may be used for purifying and disinfecting water by means of ozone gas. The method and apparatus may be used

in particular in a domestic setting for treating water prior to its use in a residence.

Water 1 is introduced into container 2 (which may be of any particular size and shape) through an inlet port, for example a
5 resealable cap 3. The cap 3 may be removably affixed to the container 2 by any suitable method, such as a screw thread or a bayonet mount. When the cap is closed, the container is sealed.

It will be appreciated that container 2 may allow some of the gas to escape there from during the treatment of water 1 (eg. some
10 of the treatment gas may exit container 2 during the treatment). In such an embodiment, the inlet port may only be partially sealed. Alternately all, or essentially all, of the fluid may be maintained in container 2 until the treatment cycle is completed and in such a case, the liquid inlet port is fully sealable.

15 The unit is provided with a source of ozone. This may be a canister of compressed ozone gas which is provided as part of the unit or fed to container 1 via a hose (not shown). Preferably, the device includes an ozone generator and the ozone generator is supplied with a source of oxygen. This source of oxygen may be the ambient air.
20 Preferably, oxygen enriched air is used. Accordingly, the unit may be connected to a source of oxygen enriched air for example the unit may be provided with a canister of compressed gas containing elevated levels of oxygen or pure oxygen, or it may be connected via a hose to such a source or, preferably, the unit may include an oxygen
25 concentrator 9, such as those which utilize pressure swing adsorption and are known in the art. Pressurized air may be provided to oxygen concentrator 9 such as by a motor driven fan, or any other manner known in the art (not shown).

The control circuit 4 of this device derives power from any
30 power source, eg. from a battery 5, by means of wire 6. The power source could also be, for example, a regular electrical outlet. A user may

activate the unit by pressing the start button 7 which sends a signal to the control circuit 4 through the wire 8.

When a cycle is initiated by pressing the start button, an off gas flow control valve 21 is opened, preferably by mechanical means. Preferably, the control valve 21 is opened through use of a lever 39, although any suitable device may be used. Further, upon initiation of a cycle, control circuit 4 preferably begins to time the cycle. Optionally, power light 27 is turned on by means of wire 28, to indicate that a cycle has been initiated.

When the unit is activated, ozone is provided to treat water 1. If the unit includes an oxygen concentrator 9 and an ozone generator 11 control circuit 4 provides power to oxygen concentrator 9 through wire 10. The pressurized gas containing oxygen 13 then flows from the oxygen rich gas source 9 through tube 14 and into ozone generator 11 where at least a fraction of the oxygen present is converted to ozone to produce ozone oxygen mixture 15. Ozone generator 11 may be any ozone generator which is known in the art. This ozone oxygen mixture 15 generated by the ozone generator then flows through a pipe 16, through a one way check 17 and into the container 2. The gas may enter the container 2 through a sparger 18 which serves to disperse the gas into fine bubbles 19. It will be appreciated that water 1 and mixture 15 may be introduced into container 2 by any method known in the art. For example, water may be introduced to container 2 via an inlet port which has a water supply (eg a hose) affixable thereto. Alternately, water 1 and mixture 2 may be introduced, either sequentially or concurrently or a combination thereof, into container 2 via a single inlet port.

After passing through the water 1 in the container 2, the gas exits the container 2 through a vent line 20. This removes gas from the head space in container 2 and prevents pressure from building up in the container 2. The vented gas passes through the off gas flow

control valve 21 and through tube 22, and into the ozone off gas sensor 23. It then passes through pipe 24, and check valve 41 into tube 43. The vented gas then enters filter 25 and into a treated water carafe 36 via tube 26 from where it may pass into the room as oxygen rich gas. Thus, the ozone off gas may serve to disinfect the filter 25 and prevent microbiological growth within the filter. Filter 25 may be any filter known in the water filtration art. Preferably, filter 25 comprises carbon.

It will be appreciated that if container 2 is at least partially sealed, eg. valve 21 is closed or at least partially closed, that pressure will build up in container 2. The increase in pressure in container 2 is beneficial in the treatment of water 1 by mixture 15. In such a case, a bleed stream of the off gases may be passed to sensor 23. Alternately, once the pressure has built up to a desired level in container 2, a steady flow of off gasses may be removed from container 21 to prevent further pressure build up in container 2.

Signals from the ozone sensor 23 are transmitted to the control circuit by any means, for example a wire 29. The control circuit 4 monitors the ozone off gas concentration by means of sensor 23.

Ozone sensor 23 measures the level of ozone in the off gas by any of those known in the art. The ozone level may be measured on an intermittent basis as water 1 is treated but is preferably continuously monitored. Control circuit 4 may be programmed with a preset valve corresponding to an amount of ozone which must be measured by sensor 23 for water 1 to be treated to a desired level. Alternately, control circuit 4 may be programmed with a concentration/time profile (ie. the treatment profile) of ozone in the off gas which must be measured by sensor 23 for water 1 to be treated to a desired level. In the latter case, during the treatment cycle the control circuit measures the amount of ozone in the off gases and compares it with preset values to monitor the progress of the water treatment. This may be based on intermittent readings or continuous readings of the ozone concentration in the off

gas or in the head space of container 2.

If the off gas concentration rises as planned (eg. in accordance with a preset range of values or in accordance with a preprogrammed concentration of ozone versus time profile in the off gas or it reaches a preset concentration for the preset time within a preset time period), control circuit 4 detects this as a successful completion of the water treatment process and may then shut down the power to the power light 27 by means of wire 28, the power to the oxygen rich gas source 9 by means of wire 10, and the power to the ozone generator 11 by means of wire 12. It may also cause the water ready light 37 to be illuminated by means of wire 38. Depressing the water dispense button 34 will send a signal to the control circuit 4 by means of wire 35 and will cause the treated water to be decanted from container 2. In one embodiment, the control circuit of this invention may be used in accordance with any method and apparatus to dispense the water from container 2. For example, the water may be poured out of cap 3. Preferably, the water is filtered, such as passing it through a filter 25. This may be achieved by a pump (not shown) or other means known in the art.

In the preferred embodiment of Figure 1, a sufficient amount of pressure is built up in container 2 to cause the water to exit container 2 and to flow through filter 25. To this end, if the treatment cycle is successfully completed, depressing the water dispense button 34 may send a signal to the control circuit 4 by means of wire 35 which causes the off gas flow control valve 21 to at least partially close, preferably fully close, such as by a mechanical member. Gas, such as from oxygen rich gas source 9, is fed to container 2. This in turn causes pressure to build up within the container 2. When the pressure reaches a preset level (eg. a sufficient amount to cause all of the water in container 2 to pass through filter 25), the water is decanted. In the preferred embodiment, this is achieved by placing a valve 40 which

opens at the preset pressure in tube 43. Thus the treated water in container 2 will be decanted when the required pressure is reached in container 2. Valve 40 may be a spring loaded check valve. The spring loaded check valve is in communication with the container 2 and the treated water carafe 36. When the check valve is opened, the treated water will flow from the container 2 through tube 43 and through the filter 25 and into the treated water carafe 36. However, it will be appreciated that container 2 may include a pressure sensor which signals control circuit 4 when the preset pressure is reached and control circuit 4 may then send a signal to open valve 40. Further, if gas is supplied to container 2 during the dispensing operation, the preset level may be sufficient, together with the supplement gas introduced into container 2 during the dispensing operation, to cause the treated water to pass through filter 25.

In a further embodiment, if the user depresses the dispense button during the delivery of water to the treated water carafe 36 or optionally during the treatment of water 1 in container 2, then another signal is preferably also sent to the control circuit 4 by means of wire 35. However, since the water treatment is not complete in this case, as a safety feature, the input will cause the off gas flow control valve 21 to be mechanically opened and the oxygen rich gas source 9 to lose power through wire 10 thereby interrupting the dispensing or treatment process. The user may then empty and refill container 2 for another treatment cycle.

Alternately, once a preset amount of time has elapsed during the dispense cycle, the control circuit 4 may interrupt the flow of gas to container 2 (eg. power to the oxygen rich gas source 9 through wire 10 may be terminated) thereby ending the dispensing process. When the user depresses start button 7 in the future, the mechanical off gas flow control valve 21 will be reset to the starting (eg. open) position for the next cycle to proceed.

If the concentration of ozone in the off gas rises too rapidly in relation to preset control values, the control circuit may detect this as a fault and may shut down the power to the power light 27 (for example by means of wire 28), the power to oxygen concentrator 9 through wire 10, and the power to ozone generator 11 through wire 12. It may also cause the system fault light 30 to be illuminated by means of wire 31 to warn the user that the water has not fully treated. As a safety feature in this circumstance, depressing water dispense button 34 will not cause water to be dispensed from container 2 (eg. button 34 may send a signal to the control circuit 4 by means of wire 35 but the input will have no effect as the existence of a system fault precludes permission to dispense the water from the container 2 to the treated water carafe 36). Light 30 will advise the user to manually empty container 2 and that the unit may require servicing.

If the off gas concentration rises too slowly in relation to preset control values (eg. too slowly compared to a preset range of values or slower than a preprogrammed concentration of ozone versus time profile in the off gas or it does not reach a preset concentration for the preset time within a preset time period), control circuit 4 may detect this as a fault and may similarly shut down the power to the power light 27 by means of wire 28, the power to the oxygen concentrator 9 through wire 10, and the power to the ozone generator 11 through wire 12. It may also cause a bad water light 32 to be illuminated by means of wire 33. Also as a safety feature in this circumstance, depressing the water dispense button 34 will send a signal to the control circuit 4 by means of wire 35 but again, the input will have no effect as the existence of an unsatisfactory treatment condition indicated to the user by light 32 being activated precludes water from being dispensed from the container 2 to the treated water carafe 36.

In one embodiment, when the filter has treated a preset number of batches, the control circuit causes a filter light (not shown)

to flash thereby warning the user that the filter must be changed soon. After a further preset number of cycles, the control circuit may also cause the filter light to be illuminated warning the consumer that the filter must be changed and that no further water will be dispensed until
5 the filter has been replaced. A sensor 44 (eg. a micro-switch mechanically in contact with filter 25) may be used to signal the control circuit 4 by a wire 45 when the filter has been removed and replaced.

It will be appreciated that many modifications may be made to the spirit of the described invention, the scope of which
10 modifications are limited only by the appended claims. For example lights 27, 30, 32 and 37 may signal a user by issuing any audio, visual or other signal which will advise a user of the specified condition. Each light may be capable of being illuminated to appear different colours so as to send alternating signals to the user thus reducing the total
15 number of lights which are required.

WE CLAIM

1. A method of treating a liquid comprising water with a gas
5 comprising ozone, the method comprising the steps of:
 - (a) providing the liquid in a treatment vessel;
 - (b) introducing the gas into the vessel to treat the liquid in the treatment vessel to obtain treated liquid;
 - (c) increasing the pressure in the treatment vessel; and
 - 10 (d) utilizing the increased pressure in the treatment vessel to dispense the treated liquid from the treatment vessel.
2. The method as claimed in claim 1 further comprising the
15 step of venting at least a portion of the gas from the treatment vessel during step (b).
3. The method as claimed in claim 2 wherein the pressure in
20 the treatment vessel is increased by reducing the amount of gas which is being vented from the treatment vessel.
4. The method as claimed in claim 1 further comprising the
step of passing the treated liquid through a filter located downstream from the treatment vessel during step (d).
- 25 5. The method as claimed in claim 4 further comprising the step of venting at least a portion of the gas from the treatment vessel during step (b) and passing at least a portion of the vented gas through the filter.
- 30 6. The method as claimed in claim 1 further comprising the step of automatically dispensing the treated water when the pressure in

the treatment vessel reaches a preset level.

7. The method as claimed in claim 1 further comprising the step of introducing the gas into the treatment vessel as bubbles.

5

8. The method as claimed in claim 1 further comprising the step of treating the liquid with the gas until a prespecified condition is met, the prespecified condition selected from the group:

10

(a) until a predetermined level of treatment of the liquid is achieved, or

(b) for a predetermined time, or

(c) until the treatment of the liquid does not match a preset treatment profile.

15

9. The method as claimed in claim 8 further comprising the step of signalling a user if a predetermined level of treatment of the liquid is not achieved in the predetermined time or if the treatment profile is not achieved.

20

10. The method as claimed in claim 8 further comprising the step of measuring the ozone concentration in the off gas in the treatment vessel and signalling a user if the concentration of ozone in the off gas is higher than that of the treatment profile.

25

11. The method as claimed in claim 8 further comprising the step of measuring the ozone concentration in the off gas in the treatment vessel and signalling a user if the concentration of ozone in the off gas is lower than that of the treatment profile.

30

12. The method as claimed in claim 1 further comprising the step of monitoring the treatment of the liquid and preventing the

liquid from being dispensed from the treatment vessel if a predetermined level of treatment of the liquid is not achieved.

13. An apparatus for treating a liquid comprising water with a
5 gas comprising ozone, the apparatus comprising:

(a) a treatment vessel having at least one inlet port for introducing the gas and the liquid into the vessel and, a gas outlet port for removing gas from the vessel;

10 (b) a pressurized source of the gas for treating the liquid in communication with gas inlet port;

(c) a first passageway for dispensing treated liquid from the treatment vessel during a dispensing cycle, the passageway having a first valve operable between a first open position and a second closed position;

15 (d) a second valve associated the gas outlet port and having a first open position for allowing the off gas to vent from the treatment vessel and a second open position for preventing the off gas to vent from the treatment vessel

20 whereby when the pressure in the treatment vessel reaches a predetermined level, the first valve automatically moves to the open position to cause treated liquid to flow from the treatment vessel through the first passageway.

25 14. The apparatus as claimed in claim 13 further comprising a filter positioned downstream from the treatment vessel and the predetermined pressure level is determined based on the pressure required to cause the treated water to flow through the filter.

30 15. The apparatus as claimed in claim 14 further comprising a second passageway in flow communication with the second valve and

the filter for venting the off gas through the filter.

16. The apparatus as claimed in claim 13 wherein the liquid in the treatment vessel is subjected to a treatment cycle and at the end of the cycle, the second valve is moved towards the closed position to increase the pressure in the treatment vessel to the predetermined level.

17. The apparatus as claimed in claim 16 wherein the second valve is a pressure actuated valve.

18. The apparatus as claimed in claim 13 further comprising an ozone generator located in flow communication with the inlet port.

19. The apparatus as claimed in claim 18 further comprising an oxygen concentrator located upstream of and in flow communication with the ozone generator.

20. The apparatus as claimed in claim 13 further comprising a controller for monitoring the treatment of the water in the treatment vessel with the gas until a prespecified condition is met, the prespecified condition selected from the group:

- (a) until a predetermined level of treatment of the liquid is achieved, or
- (b) for a predetermined time, or
- (c) until the treatment of the liquid does not match a preset treatment profile.

21. The apparatus as claimed in claim 20 further comprising a warning signal to advise a user if a predetermined level of treatment of the liquid is not achieved in the predetermined time or if the treatment

profile is not achieved.

22. The apparatus as claimed in claim 20 further comprising a sensor for measuring the ozone concentration in the off gas in the treatment vessel and a warning signal for advising a user if the concentration of ozone in the off gas is higher than that of the treatment profile.

23. The apparatus as claimed in claim 20 further comprising a sensor for measuring the ozone concentration in the off gas in the treatment vessel and a warning signal for advising a user if the concentration of ozone in the off gas is lower than that of the treatment profile.

24. The apparatus as claimed in claim 13 further comprising an actuator for commencing the dispensing cycle, a controller for monitoring the treatment of the liquid and preventing the liquid from being dispensed from the treatment vessel if a predetermined level of treatment of the liquid is not achieved.

ABSTRACT OF THE DISCLOSURE

A method for treating a liquid comprising water with a gas
5 comprising ozone comprises introducing the liquid to be treated into a
treatment vessel, introducing the gas to treat the liquid into the
treatment vessel and treating the liquid in the treatment vessel,
pressurizing the treatment vessel and, using the pressure in the
treatment vessel to dispense the treated liquid from the treatment
10 vessel through a filter. An apparatus for treating the liquid is also
disclosed.

The diagram illustrates a water supply system for a building. At the bottom, a pump station (4) is connected to a main distribution line (5). This line branches into two paths: one leading to a storage tank (20) and another leading to a series of vertical risers (11, 14, 13, 9). The storage tank (20) is equipped with a float valve (3) and a pump (2). A pump (40) is also shown on the line connecting the tank to the distribution network. The system includes various components labeled with numbers: 1 (water level), 2 (pump), 3 (float valve), 4 (pump station), 5 (main line), 6 (valve), 7 (valve), 8 (line), 9 (riser), 10 (line), 11 (riser), 12 (line), 13 (riser), 14 (riser), 15 (valve), 16 (valve), 17 (valve), 18 (valve), 19 (valve), 20 (storage tank), 21 (valve), 22 (line), 23 (valve), 24 (line), 25 (valve), 26 (line), 27 (valve), 28 (valve), 29 (line), 30 (valve), 31 (valve), 32 (valve), 33 (valve), 34 (valve), 35 (line), 36 (valve), 37 (valve), 38 (valve), 39 (valve), 40 (pump), 41 (pump), 42 (line), 43 (line), 44 (valve), 45 (line).

BERESKIN & PARR

BOX 401, 40 KING STREET WEST, TORONTO, CANADA M5H 3Y2
PHONE (416) 364-7311 • FAX (416) 361-1398 • WWW.BERESKINPARR.COM

Please type a plus sign (+) inside this box → +

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number 5562-740/PMdC	
	First Named Inventor CONRAD et al	
	COMPLETE IF KNOWN	
	Application Number	n/a
	Filing Date	n/a
	Group Art Unit	n/a
<input type="checkbox"/> Declaration Submitted with Initial Filing OR <input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)		Examiner Name n/a

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD AND APPARATUS FOR PURIFYING WATER

the specification of which (Title of the Invention)

☒ is attached hereto

OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
2,253,689	CANADA	NOVEMBER 9, 1998	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer Number Bar Code Label here

Name	Registration Number	Name	Registration Number
Daniel R. Bereskin	22,257	H. Samuel Frost	31,696
Richard J. Parr	22,836	Philip Mendes da Costa	33,106
H. Roger Hart	26,426	Robert B. Storey	33,108
David W.R. Langton	27,747	John R. Rudolph	38,003
C. Lloyd Sarginson	29,245	Robin L.A. Coster	38,016
Timothy J. Sinnott	31,083	Michael E. Charles	38,036

☒ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number OR ☒ Correspondence address below

Name	Bereskin & Parr				
Address	Box 401				
Address	40 King Street West				
City	Toronto	State	Ontario	ZIP	M5H 3Y2
Country	Canada	Telephone	(416) 364-7311	Fax	(416) 361-1398

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: ☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname	
WAYNE ERNEST		CONRAD	
Inventor's Signature	<i>Wayne Conrad</i>		Date
Residence: City	HAMPTON	State	ONTARIO
		Country	CANADA
Post Office Address	27 KING STREET		
Post Office Address	AS ABOVE		
City	HAMPTON	State	ONTARIO
		ZIP	L0B 1J0
		Country	CANADA

☐ Additional inventors are being named on the ☒ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

AN-28-99 19:20 From:

9052638131

T-896 P.01 Job-919

Please type a plus sign (+) inside this box → ☐

PTO/SB/C2A (3-97)
 Approved for use through 9/30/98. OMB 0551-0032
 Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION
ADDITIONAL INVENTOR(S)
 Supplemental Sheet
 Page ___ of ___

Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
HELMUT GERHARD				CONRAD			
Inventor's Signature	<i>Helmut Conrad</i>					Date	28/1/99
Residence: City	HAMPTON	State	ONTARIO	Country	CANADA	Citizenship	CANADIAN
Post Office Address	27 KING STREET						
Post Office Address	AS ABOVE						
City	HAMPTON	State	ONTARIO	ZIP	L0B 1J0	Country	CANADA
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
TED				SZYLOWIEC			
Inventor's Signature	<i>Szylowiec Ted</i>					Date	28/1/99
Residence: City	HAMPTON	State	ONTARIO	Country	CANADA	Citizenship	CANADIAN
Post Office Address	27 KING STREET						
Post Office Address	AS ABOVE						
City	HAMPTON	State	ONTARIO	ZIP	L0B 1J0	Country	CANADA
Name of Additional Joint Inventor, if any:				<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))				Family Name or Surname			
Inventor's Signature						Date	
Residence: City		State		Country		Citizenship	
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

